

## TECHNICAL INFORMATION FOR **ECO D 03**

TYPE:	Solution of silicone with various molecular masses
DELIVERY SHAPE:	The solution in organic solvents
FEATURES AND USE:	<p><b>ECO D 03</b> is used as a separator in the casting industry. It is used during the metal casting. The silicone film adheres well to the treated surface and completely prevents bonding. Advantages of <b>ECO D 03</b> over the other products of the same purposes are:</p> <ul style="list-style-type: none"><li>- Low consumption,</li><li>- Chemical inertness,</li><li>- A large number of working cycles,</li><li>- Longer lifetime of the molds and forms.</li></ul> <p>Surfaces treated with this means remain unchanged and physiologically and ecologically serviceable.</p>
PREPARATION FOR APPLICATION:	<p><b>ECO D 03</b> is applied in a delivered form. The surface of mold on which the means is applied should be dry and completely clean.</p>
APPLICATION METHOD:	<p><b>ECO D 03</b> is applied to the surface by spraying or coating using pneumatic sprayer, mop, sponge etc. in one layer as thin as possible. The processing is performed once, and the excess of means has to be removed. Moulds and forms are exploited immediately after the application of means.</p> <p><b>ECO D 03</b> consumption: 0,05-0,15L/m<sup>2</sup>.</p>
SAFEGUARD MEASURES:	<p><b>ECO D 03</b> is the solution in organic solvents, it is flammable, so its application must comply with fire safety measures, as when applying similar products that contain flammable solvents. For professional use only!</p>
PACKAGING:	200L Metal barrels, 10L plastic cans and 1L plastic bottles.
STORAGE:	<p><b>ECO D 03</b> should be stored outdoors and indoors away from the heat sources.</p>
PRODUCT LIFETIME:	<p><b>ECO D 03</b> can be kept indefinitely in the original packaging.</p>